



The GCM-302 mini clamp meter is aimed at small to medium-sized cable measurements. Tapered jaws, slim profile, and a light 200g weight allow reaching cables in tight places. Additional features, such as Auto Ranging, Auto Power Off, Max Hold and Maximum Load let professionals focus on the target application while the GCM-302 takes care of the measuring.

## GCM-302



### FEATURES

- \* Auto Range
- \* Auto Power Off
- \* Max Hold
- \* 600A/600V Max Input
- \* Mini Size
- \* High Accuracy
- \* MAX Clamp Size : Ø30mm

### SPECIFICATIONS

#### ACA

<b>Range</b>	200A, 600A
<b>Resolution</b>	0.1A, 1A
<b>Accuracy</b>	±(1.9%rdg+5dgts)~±(1.9%rdg+10dgts)
<b>Frequency</b>	50Hz~500Hz

#### ACV

<b>Range</b>	2V, 20V, 200V, 600V
<b>Resolution</b>	0.001V, 0.01V, 0.1V, 1V
<b>Accuracy</b>	±(1.5%rdg+5dgts)~±(1.5%rdg+10dgts)
<b>Input Impedance</b>	Approx.11MΩ~Approx.10MΩ
<b>Frequency</b>	40Hz~500Hz

#### DCV

<b>Range</b>	200mV, 2V, 20V, 200V, 600V
<b>Resolution</b>	0.1mV, 0.001V, 0.01V, 0.1V, 1V
<b>Accuracy</b>	±(0.7%rdg+3dgts)~±(1.3%rdg+3dgts)
<b>Impedance</b>	Approx.11MΩ~Approx.10MΩ

#### Ohm

<b>Range</b>	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ
<b>Resolution</b>	0.1Ω, 0.001kΩ, 0.01kΩ, 0.1kΩ, 0.001MΩ, 0.01MΩ
<b>Accuracy</b>	±(1.5%rdg+5dgts)~±(10%rdg+5dgts)
<b>Open-Loop Voltage</b>	Approx.0.4V

#### DIODE

<b>Range</b>	2V
<b>Resolution</b>	0.001V
<b>Accuracy</b>	±(10%rdg+5dgts)
<b>Open-Loop Voltage</b>	Approx.1.5V

#### BUZZER

<b>Range</b>	200Ω
<b>Resolution</b>	0.1Ω
<b>Accuracy</b>	The buzzer turns on for resistances lower than 60Ω±20Ω
<b>Open-Loop Voltage</b>	0.4V

#### OPERATION TEMPERATURE / HUMIDITY

0°C~50°C (32°F~122°F)/Below 80% R.H. (No Condensation)

#### STORAGE TEMPERATURE / HUMIDITY

-10°C~60°C (14°F~140°F)/Below 70% R.H. (No Condensation)

#### DIMENSIONS & WEIGHT

189(L) x 71(W) x 37(H) mm ; Approx. 200g (Including Batteries)

### ORDERING INFORMATION

**GCM-302** Mini Clamp Meter

#### ACCESSORIES :

User manual x 1, Test leads, Carrying case



The GCM-303 mini clamp meter, like the GCM-302 has all the features of a standard multimeter, yet also has true RMS. Featuring tapered jaws, a wide range (600A, 600V max input), high accuracy and the ability to automatically power down make the GCM-303 suitable for almost any cable measurement task. Small enough to fit in a pocket and light enough to carry, the GCM-303 is the ideal multipurpose mini clamp meter.

## GCM-303



### FEATURES

- \* Auto Range
- \* Auto Power Off
- \* Max Hold
- \* True RMS Measurement
- \* 600A/600V Max Input
- \* Mini Size
- \* High Accuracy
- \* MAX Clamp Size : Ø30mm

SPECIFICATIONS	
<b>ACA</b>	
Range	200A, 600A
Resolution	0.1A, 1A
Accuracy	±(1.9%rdg+5dgts)~±(1.9%rdg+10dgts)
Frequency	50Hz~500Hz
<b>ACV</b>	
Range	2V, 20V, 200V, 600V
Resolution	0.001V, 0.01V, 0.1V, 1V
Accuracy	±(1.5%rdg+5dgts)~±(1.5%rdg+10dgts)
Input Impedance	Approx.11MΩ~Approx.10MΩ
Frequency	40Hz~500Hz
<b>DCV</b>	
Range	200mV, 2V, 20V, 200V, 600V
Resolution	0.1mV, 0.001V, 0.01V, 0.1V, 1V
Accuracy	±(0.7%rdg+3dgts)~±(1.3%rdg+3dgts)
Impedance	Approx.11MΩ~Approx.10MΩ
<b>Ohm</b>	
Range	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ
Resolution	0.1Ω, 0.001kΩ, 0.01kΩ, 0.1kΩ, 0.001MΩ, 0.01MΩ
Accuracy	±(1.5%rdg+5dgts)~±(10%rdg+5dgts)
Open-Loop Voltage	Approx.0.4V
<b>DIODE</b>	
Range	2V
Resolution	0.001V
Accuracy	±(10%rdg+5dgts)
Open-Loop Voltage	Approx.1.5V
<b>BUZZER</b>	
Range	200Ω
Resolution	0.1Ω
Accuracy	The buzzer turns on for resistances lower than 60Ω±20Ω
Open-Loop Voltage	0.4V
<b>OPERATION TEMPERATURE / HUMIDITY</b>	
0°C~50°C (32°F~122°F)/Below 80% R.H. (No Condensation)	
<b>STORAGE TEMPERATURE / HUMIDITY</b>	
-10°C~60°C (14°F~140°F)/Below 70% R.H. (No Condensation)	
<b>DIMENSIONS &amp; WEIGHT</b>	
189(L) x 71(W) x 37(H) mm ; Approx. 200g (Including Batteries)	

### ORDERING INFORMATION

**GCM-303** Mini Clamp Meter with True RMS Measurement

#### ACCESSORIES :

User manual x 1, Test leads, Carrying case